

Potato Harvester (SGPH 200)

SHAKTIMAN - **GRIMME**



Effective separation of haulm and potatoes

High acreage performance

Especially for small-structured cultivation areas

Root Crop Solutions

Potato Harvester (SGPH 200)



Gentle filling



A hydraulic folding mechanism lifts the conveyor outlet out of the crop flow and thus enables the filling of transport vehicle.

Crop protection



Main webs with lug conveyor for optimum gentle crop handling. Gentle crop transfer.

High acreage performance and separating effect



Wider first main web for an effective sieving. Haulm separation with wide roller & adjustable finger for an optimum setting for the trash separation.

Picking Table



Wide 2nd web used as picking table to separate unwanted particles from the tubers over the whole length works efficiently

Perfectly comfortable



Operator friendly analog operation, clear visibility of main webs, to enable an optimum machine operation.

Integrated rollers for Trash separation



Adjustable finger for an optimum setting for the trash separation with integrated roller.

Advantages

- Simple operation, setting and maintenance
- Everything in sight: Excellent visibility to the digging unit during harvest.
- Gentle transport of the crop without any friction.
- The compact design and Proven, reliable technology.

SHAKTIMAN-GRIMME ROOT CROP SOLUTIONS PRIVATE LIMITED

"SHAKTIMAN", Nr. Bharudi Toll Plaza, Bhunava Village, NH-27,
Taluka : Gondal, District : Rajkot - 360311, Gujarat, India.

☎ 99252 50169 ✉ info@shaktiman-grimme.com 🌐 www.shaktiman-grimme.com

📘 shaktimangrimme.official 📺 shaktimangrimmeofficial

For More Information Call: ☎

Gujarat - 99250 29707

Punjab & Haryana - 94170 56026

Uttar Pradesh - 95205 59000

Parameter	Dimension
No. of Rows	2
Working Depth	130-200 mm
Working Width	1400 mm
Speed of Operation	1.0 – 2.0 km/h
Pickup (Front dig) Conveyor (L x W)	4070 x 1360 mm
Elevator Conveyor (L x W)	8600 x 600 mm
Separator (Crop Selection) Conveyor	3330 x 970 mm
Drop Height*	360 mm (Adjustable)
Overall Length	4920 mm
Overall Width	1920 mm
Overall Height	2730 mm
Total Weight	2400 kg
PTO Input speed	540 rpm
Tractor Power required (kW/hp)	41/55 & Above
Rotor Shaft Speed**	175 rpm

* Specifications can be changed at any time.
Accessories shown are not part of the standard fitment.

Root Crop Solutions